
Tubular cable lugs, Cu, F-series





- For fine and superfine stranded round conductors, e.g. to DIN EN 60228 Cl. 5 and 6
- Pipe dimension adjusted for fine and superfine stranded conductors
- Special wide opening for the easy entry of fine conductors

Characteristics

- Annealed material optimises material and crimping properties
- To DIN EN 61373 class 1B vibration-tested
- Simple and safe connection due to flat contact surfaces and internal chamfer
- Reliable assignment owed to item designation on the cable lug

Material

- Copper (EN13600)

Surface

- Tin-plated to protect against corrosion

Technical instructions

- Tool: see page 42

Additional information

- Possible as a special bright version on request. Part Number appendix „BK“
- 10 - 240 mm² UL-tested

Nominal cross section mm²	Size of bolt dia.	Part No.	Dimension mm								Weight/ 100 pcs. ~ kg	Packing unit/pcs
			d1	a	b	d2	d4	c1	c2	l		
10	M5	**702F5**	5.5	14	12	5.5	8.0	6.25	7.5	27	0.72	100
	M6	**702F6**	5.5	14	12	6.5	8.0	6.25	7.5	27	0.71	100
	M8	**702F8**	5.5	14	16	8.4	8.0	9.00	9.5	29	0.77	100
	M10	**702F10**	5.5	14	16	10.5	8.0	10.50	11.5	31	0.82	100
	M12	**702F12**	5.5	14	19	13.0	8.0	12.00	13.0	32	0.82	100
16	M5	**703F5**	6.6	15	13	5.5	9.5	6.25	7.5	30	1.10	100
	M6	**703F6**	6.6	15	13	6.4	9.5	6.25	7.5	30	1.07	100
	M8	**703F8**	6.6	15	16	8.4	9.5	10.00	10.0	32	1.21	100
	M10	**703F10**	6.6	15	17	10.5	9.5	12.00	12.0	34	1.28	100
	M12	**703F12**	6.6	15	19	13.0	9.5	13.00	13.0	35	1.28	100
25	M5	**704F5**	7.9	17	15.5	5.3	11.0	7.50	7.5	32	1.52	25
	M6	**704F6**	7.9	17	15.5	6.5	11.0	7.50	7.5	32	1.50	100
	M8	**704F8**	7.9	17	17	8.4	11.0	10.00	10.0	34	1.61	100
	M10	**704F10**	7.9	17	17	10.5	11.0	12.00	12.0	37	1.71	100
	M12	**704F12**	7.9	17	19	13.0	11.0	13.00	13.0	38	1.74	25
35	M6	**705F6**	9.2	19	17.5	6.4	12.4	7.50	7.5	35	1.91	100
	M8	**705F8**	9.2	19	18	8.4	12.4	10.00	10.0	37	2.08	100
	M10	**705F10**	9.2	19	18	10.5	12.4	12.00	12.0	40	2.24	100
	M12	**705F12**	9.2	19	19	13.0	12.4	13.00	13.0	41	2.22	25
	M14	**705F14**	9.2	19	21	15.0	12.4	14.50	14.5	43	2.41	25
50	M6	**706F6**	11.0	21	21	6.4	15.0	10.00	10.0	41	3.54	25
	M8	**706F8**	11.0	21	21	8.4	15.0	10.00	10.0	41	3.44	50
	M10	**706F10**	11.0	21	21	10.5	15.0	12.00	12.0	43	3.64	50
	M12	**706F12**	11.0	21	21	13.0	15.0	13.00	13.0	46	3.73	50
	M14	**706F14**	11.0	21	23	15.0	15.0	14.50	14.5	48	3.89	25
	M16	**706F16**	11.0	21	28	17.0	15.0	16.00	16.0	50	4.02	25

See next page