
Insulated solderless terminals





- For fine and superfine stranded conductors, e.g. to DIN EN 60228 Cl. 5 and 6
- To DIN 46237
- High-quality brazing process in the crimp area
- Insulation sleeve halogen-free

Characteristics
- Heat resistant to 105° C
- Easy-Entry insulation for simple cable insertion
- Cross-section-dependent colour-coding

Material
- Copper (ETP)
- Insulation sleeve: PA

Surface
- Tin-plated to protect against corrosion

Technical instructions
- Tool: see page 173

Additional information
- * = not standardised
- 0.1 - 0.4 mm² not CSA-tested

Nominal cross section mm²	Nominal size to DIN	Part No.	Colour	Hint	Dimension mm								Weight/ pcs. ~kg	Packing unit/pcs
					a1	a2	d1	d2	d3	d4	l	s		
0.1 - 0.4	--	**6192**		*	--	--	1.0	2.3	5.0	2.2	14.0	0.5	0.020	100
	--	**61925**		*	--	--	1.0	2.6	5.0	2.2	14.0	0.5	0.020	100
	--	**6193**		*	--	--	1.0	3.3	5.0	2.2	14.0	0.5	0.020	100
	--	**61935**		*	--	--	1.0	3.8	6.5	2.2	16.0	0.5	0.025	100
	--	**6194**		*	--	--	1.0	4.4	7.0	2.2	16.0	0.5	0.025	100
	--	**6195**		*	--	--	1.0	5.4	8.0	2.2	15.0	0.5	0.025	100
0.5 - 1	2.5 - 1	**62025**			5	10.5	1.6	2.8	6.0	4.5	16.5	0.8	0.060	100
	3.0 - 1	**6203**			5	10.5	1.6	3.2	6.0	4.5	16.5	0.8	0.060	100
	3.5 - 1	**62035**			5	10.5	1.6	3.7	6.0	4.5	16.5	0.8	0.550	100
	4.0 - 1	**6204**			5	10.5	1.6	4.3	8.0	4.5	17.5	0.8	0.070	100
	5.0 - 1	**6205**			5	10.5	1.6	5.3	10.0	4.5	18.5	0.8	0.090	100
	--	**6206**		*	5	10.5	1.6	6.5	11.0	4.5	20.5	0.8	0.080	100
	--	**6208**		*	5	10.5	1.6	8.4	14.0	4.5	22.5	0.8	0.130	100
	--	**62010**		*	5	10.5	1.6	10.5	18.0	4.5	24.5	0.8	0.130	100
1.5 - 2.5	3.0 - 2.5	**6303**			5	11.5	2.3	3.2	6.0	5.0	17.5	0.8	0.065	100
	3.5 - 2.5	**63035**			5	11.0	2.3	3.7	6.0	5.1	17.5	0.8	0.065	100
	4.0 - 2.5	**6304**			5	11.5	2.3	4.3	8.0	5.1	18.5	0.8	0.080	100
	5.0 - 2.5	**6305**			5	11.5	2.3	5.3	10.0	5.1	20.5	0.8	0.090	100
	6.0 - 2.5	**6306**			5	11.5	2.3	6.5	11.0	5.1	22.5	0.8	0.110	100
	8.0 - 2.5	**6308**			5	11.5	2.3	8.4	14.0	5.1	23.5	0.8	0.130	100
	--	**63010**		*	5	11.5	2.3	10.5	18.0	5.1	25.5	0.8	0.160	100
4 - 6	4.0 - 6	**6504**			6	12.5	3.6	4.3	8.0	6.5	20.5	1.0	0.140	100
	5.0 - 6	**6505**			6	12.5	3.6	5.3	10.0	6.5	21.5	1.0	0.160	100
	6.0 - 6	**6506**			6	12.5	3.6	6.5	11.0	6.5	22.5	1.0	0.170	100
	8.0 - 6	**6508**			6	12.5	3.6	8.4	14.0	6.5	25.5	1.0	0.220	100
	10.0 - 6	**65010**			6	12.5	3.6	10.5	18.0	6.5	27.5	1.0	0.290	100