# CN3201220


Modular contactor, three-pole or four-pole, 32A AC1, 220...230VAC (3NO+1NC)




| | | | |
|---|---|---|---|
| Product designation | | | MODULAR CONTACTOR |
| Product type designation | | | CN |
| Operating voltage type | | | AC/DC |
| Number of poles | | | 4 |
| Number of DIN modules | | | 2 |
| **Electrical features** | | | |
| IEC Conventional free air thermal current Ith | | A | 32 |
| Operational current AC1 and AC-7a ≤400V | | A | 32 |
| Operational current AC3 and AC-7b ≤400V | | A | 8.5 |
| Rated insulation voltage Ui IEC/EN | | V | 440 |
| Rated impulse withstand voltage Uimp | | kV | 4 |
| Minimum switching capacity | | | ≥17V ≥50mA |
| Power dissipation per pole (average value) Ith | | W | 2.5 |
| **Control circuit** | | | |
| Auxiliary rated supply voltage Us | | | 220VAC/VDC |
| Auxiliary contacts | | | |
| | NO | Nr. | 3 |
| | NC | Nr. | 1 |
| Average coil consumption ≤20°C | | | |
| | in-rush | W | 3 |
| | holding | W | 3 |
| Operating voltage | | | |
| pick-up | | | |
| | min | %Us | 85 |
| | max | %Us | 110 |
| drop-out | | | |
| | min | %Us | 20 |
| | max | %Us | 75 |
| **Operating times** | | | |
| Average time | | | |
| Closing NO | | | |
| | min | ms | 15 |
| | max | ms | 45 |
| Opening NO | | | |
| | min | ms | 20 |
| | max | ms | 70 |
| **Operations** | | | |
| Mechanical life | | cycles | 3000000 |
| Electrical life AC3 | | cycles | 500000 |
| Electrical life AC1 | | cycles | 150000 |
| **Ambient conditions** | | | |
| Operating temperature | | | |
| | min | °C | -15 |
| | max | °C | 55 |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

| | | | | |
|---|---|---|---|---|
| Storage temperature | | | | |
| | | min | °C | -30 |
| | | max | °C | 80 |
| Max altitude | | | m | 2000 |
| **Mechanical features** | | | | |
| Fixing | | | | DIN rail 35mm |
| Tightening torque for coil terminal | | | | |
| | | max | Nm | 0.6 |
| | | max | lbin | 0.6 |
| Tightening torque for terminals | | | | |
| | | max | Nm | 1.2 |
| | | max | lbin | 0.9 |
| Conductor section | | | | |
| | Coil terminal | | | |
| | | min | mm² | 1 |
| | | max | mm² | 2.5 |
| | Power terminal | | | |
| | | min | mm² | 1 |
| | | max | mm² | 10 |
| Terminals tool | | | | PZ2 |
| Weight | | | g | 260 |
| **Resistance & Protection** | | | | |
| Frontal IP degree | | | | IP20 |
| Pollution degree | | | | 3 |
| **Dimensions** | | | | |




## Wiring diagrams





The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

## Certifications and compliance

Compliance

| |
|---|
| IEC/EN 60947-1 |
| IEC/EN 60947-4-1 |
| IEC/EN 60947-5-1 |
| IEC/EN 61095 |

Certificates

EAC

## ETIM classification

| | |
|---|---|
| ETIM 8.0 | EC000066 - Power contactor, AC switching |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding