
MiniBridge

1.27 mm Connectors







Downloaded from Arrow.com.

MiniBridge - CABLE CONNECTOR SYSTEMS

The compact design of the single-row cable connector systems in a 1.27 mm pitch is excellent for space-saving connections between PCBs and decentralised function units such as operator panel displays, switches, motors, fans or fuses. The single row MiniBridge connector Koshiri version with a 1.27 mm pitch offers a high level of mating reliability. The housing geometry helps to avoid damage of the male contacts even in case of improper skewed insertion. In addition to Koshiri Secure*, the MiniBridge connector fulfils the applicable requirements of LV214 for automotive connectors in Insulation Displacement Connection (IDC) technology. The cable connector system is used in various fields for example, automobile industry, mechanical engineering, medical technology and also consumer electronics. Various connection options can be realised thanks to the right angle or vertical male connectors and female connectors with 90° and 180° cable outlets. Both female and male connectors in Surface Mount Technology (SMT) and IDC variants are available. The plastic housing is resistant to temperatures up to 150 °C whereby the connector is suitable for lead-free reflow soldering. The male connectors are available as tape and reel packaging for automatic assembly.

The cable guide of the female connector simplifies cable connection or individual wires. Prefabricated cables are available in stock. Specified assemblies are realised within a short time period.



MiniBridge Connectors Standard



MiniBridge Connectors Koshiri

*Requirement for Koshiri Secure:
Signal and current carrying components (contacts) may only be touched by their signal and current carrying opposites (and their catch funnels) during assembly/disassembly. Contact with housing components is structurally not permitted. (Source LV 214)

Downloaded from Arrow.com.

AVAILABLE TERMINATIONS



- Vertical male - Female with 90° cable outlet



- Right angle male - Female with 90° cable outlet



- Right angle male - Female with 180° cable outlet



- Vertical male - Female with 180° cable outlet

Downloaded from Arrow.com.

FEATURES

Easy Assembly

- Pick-and-place cover for automatic assembly with a vacuum pipette.
- Reliable retention force due to ruggedized metal clips on both sides of each male.



Guiding Elements

- The rugged insulation body of the male connector provides an excellent cable connector guide.
- Two pegs (round and oval) for exact positioning on the printed circuit board (pcb).



Interlocking

- Positive lock (red):
  (high vibration/Shock load) unlockable only with a tool, e.g. tip of pen
- Friction lock (black):
  (normal vibration/shock load) unlockable without any tool



SSL-Lighting Technology

- Connectors with colourless insulation bodies helps prevent shadow formation in lighting applications, e.g. LED strips with transparent diffusion disks. Thus providing uniform light distribution.



Downloaded from Arrow.com.

ELECTRICAL AND MECHANICAL CHARACTERISTICS SMT AND IDC

Technical Data

Description	Standard	Male Connector SMT Type A and P	Female Connector SMT Type P	Male Connector IDC Type P	Female Connector IDC Type A and P
Climate category	DIN EN 60068-1 test b	55 / 150 / 56	55 / 125 / 56	55 / 150 / 56	
Temperature range		-55 / 150 °C	-55 / 125 °C	-55 / 150 °C	
Current rating per contact	IEC60512 test 5b	see IDC or SMT female connector	20 C° max. 4.8 A 70 C° max. 3.2 A 100 C° max. 2.0 A	see IDC or SMT female connector	20 C° max. 8.7 A 70 C° max. 6.8 A 100 C° max. 5.4 A depends on cable
Air- and creepage distance		contact - contact 0.4 mm			
Operating voltage	IEC 60664	The permissible operating voltages depend on the customer application and on the applicable or specified safety requirements. Insulation coordination according to IEC 60664-1 has to be regarded for the complete electrical device. Therefore, the maximum creepage and clearance distances of the mated connectors are specified for consideration as a part of the whole current path. In practice, reductions in creepage or clearance distances may occur due to the conductive pattern of the printed board or the wiring used, and have to be taken into account separately. As a result the creepage and clearance distances for the application may be reduced compared to those of the connector.			
Dielectric strength	IEC 60512 test 4a	contact – contact 500 V_{rms}			
Contact resistance	IEC 60512 test 2a	≤ 25 mΩ			
Insulation resistance	IEC 60512 test 3a	≥ 10^4 MΩ			
Vibration, sine	IEC 60512 test 6d	10 – 2000 Hz 20 g			
Contact disturbance (while vibration test)	IEC 60512 test 2e	< 1 µs			
Shock halfsine	IEC 60512 test 6c	50 g 11 ms			
Mechanical operation	IEC 60512 test 9a	500 mating cycles			
Insertion and withdrawal force	IEC 60512 test 13b	1 N per contact			
Gauge retention force	IEC 60512 test 16e	> 0.1 N			
Polarization	IEC 60512-13-5	60 N			
Interlocking noise				40 dB (A)	

Downloaded from Arrow.com.

ELECTRICAL AND MECHANICAL CHARACTERISTICS CABLE

Cable Data

Description	Standard Cable (PVC)	High Temperature Cable (TPE-ET)	Halogen-free Cable (TPE-O)
Cross Section	AWG-26/ 7/ 0.14 mm^2		
Conductor	Cu wire tin-plated		
Marking	available		
Insulation	PVC wall thickness min. 0.178 mm	TPE-ET wall thickness min. 0.2 mm	Polyolefin wall thickness min. 0.178 mm
Shore hardness	94 ±3 (Shore A)	96 ±3 (Shore A)	90 ±3 (Shore A)
Technical data			
Temperature range	-30/105 °C (unmoved) -20/105 °C (moved)	-60/125 °C (unmoved) -40/125 °C (moved)	-40/105 °C (unmoved) -20/105 °C (moved)
Voltage rating	max. 300 V		
Dielectric strength	2000 V_{rms}	1500 V_{rms}	1500 V_{rms}
Conductor resistance	≤ 135 Ω/km	≤ 138 Ω/km at 20 °C	max. 135 Ω/km at 20 °C
Insulation resistance	≥ 100 MΩ x km at 20 °C	≥ 20 MΩ x km at 20 °C	min. 20 MΩ x km at 20 °C
Capacitance at 1 kHz	GSG ≤ 60 pF/m	GSG 40 pF/m	GSG 40 pF/m
Inductance	GSG 0.9 µH/m at 10 KHz	GSG 0.79 µH/m at 10 KHz	GSG 0.95 µH/m at 1 KHz
Impedance	GSG 100 Ω	GSG 110 Ω	GSG 95 Ω
Crosstalk in %	Cable length 3 m: NE 5.4 / FE 6.8	–	–
Propagation delay	4.6 ns/m	6.2 ns/m	–
Flammability	UL VW-1; CSA FT-1	UL 1581 Sec. 1080, VW-1	UL 1581
Product-approval			
UL	AWM 2651	– *	AWM 21151
CSA	Yes	No	Yes

* UL Style 21739 on request

For more information on tooling, variation and processing of cable please check **Processing Specification MiniBridge IDC**

Downloaded from Arrow.com.


VERTICAL MALE SMT TYPE P


Product Specification

- SMT termination
- tape and reel packaging for automatic assembly
- suitable for lead-free reflow soldering process
- with pick-and-place cover
- for available part numbers please refer to our website




Dimensional Drawings






No. of Contacts	A	B	C
2	5.69	7.62	5.60
3	6.96	8.89	6.79
4	8.23	10.16	8.06
6	10.77	12.70	10.60
8	13.31	15.24	13.14
10	15.85	17.78	15.68
12	18.39	20.32	18.22

All dimensions in mm



Recommended Layout




Downloaded from Arrow.com.


CABLE ASSEMBLIES

Product Specification

- IDC termination
- Ribbon cable AWG 26/7
- Discrete wire AWG 22/7, AWG 24/7 and AWG 26/7
- for available part numbers please refer to our website



Dimensional Drawings



No. of Contacts	A
2	7.62
3	8.89
4	10.16
6	12.70
8	15.24
10	17.78
12	20.32

All dimensions in mm

Downloaded from Arrow.com.

Connect With Us

We make it easy to connect with our experts and are ready to provide all the support you need.
Visit **www.te.com/support** to chat with a Product Information Specialist.

te.com

2022 TE Connectivity. All Rights Reserved.

TE Connectivity, TE connectivity (logo), ERNI, MiniBridge and Every Connection Counts are trademarks owned or licensed by the TE Connectivity family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

074560 03/22 Original

CATALOG

TE Connectivity

ERNI Electronics GmbH & Co. KG
Seestraße 9
73099 Adelberg
Germany

Tel +49 7166 50-0
www.te.com
www.erni.com

Downloaded from Arrow.com.