CAT. N° 4 125 05



POWER CONTACTOR CX³ - WITH 24 V~ COLL - 2P 250 V~ - 25 A - 2 N/O

Pack (number of units)	1
Volume (dm³)	0,211
Weight (g)	131,00

Product characteristics

Power contactors with 24 V~ coil

2-pole - 250 V~

- I max : 25 A
- Type of contact : 2 N/O
- Number of modules : 1

General characteristics

Power contactors without handle CX³ - from 16 A to 63 A

- Conform to IEC/EN 61095
- Space for power supply busbar on top (up to 25 A)

Documentation

Catalogue pages & additional information

- Description page (p.087)
- Technical page (p.088)
- Dimensions of din-rail equipment

Agreements & certificates of conformity

- NF-NF012_2632
- VDE-40029913
- OC / CB-CB FR_709436

Installation & technical data

- F01332EN-03

Environmental product profile

- Environnemental product sheet n°8 E0007B-FR
- LGRP-00980-V02
- LGRP-2015-302-v1-EN

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.