



Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT










Anforderungsstufe 1
performance level 1

Kontaktbereich vergoldet
mating area gold plating


Anschlussbereich verzinnt 4-6 µm
terminal area 4-6 µm tin plating






Koplanarität der Anschlüsse ≤ 0,1 mm
coplanarity area of termination ≤ 0,1 mm

Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
tape on reel packaging according to DIN IEC 60286-3
Verpackungseinheit: 440 Stück
packaging unit: 440 pcs



Abspulrichtung - *reel off direction*



454195-E		weiß *white*	0,6	6,6	1,2	6,0	Codierung wie Variante schwarz *Encoding such variant black*
254702-E		rot *red*	4,2	3,0	4,8	2,4	
254701-E		grün *green*	3,0	4,2	3,6	3,6	
254700-E		blau *blue*	1,8	5,4	2,4	4,8	
254699-E		schwarz *black*	0,6	6,6	1,2	6,0	
Ident-Nr. *part-no.*	Codierung *coding*	Farbe *color*	A	B	C	D	Bemerkung *note*

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Geschmacksmustereintragung vorbehalten.
The reproduction and distribution of this document as well as the exploitation and communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

Die deutsche Version dieser Zeichnung dient nur zur Erleichterung der Handhabung. Bei Abweichungen vom dem englischen Original gilt das englische Original.
The German version of this drawing has been offered for convenience only and may deviate from the english original.
In case of any deviation the English version shall prevail.

Dimension no.	Tolerances ISO 8015	All Dimensions in mm	Scale 3:1	
			Material	siehe Tabelle
Customer drawing: This Drawing is a controlled Document.	Subject to modification without prior notice. Drawing will not be updated.		M 2,54 SRC-A, 6-polig	
e1 / Index	10.05.2023 / Date	TE Connectivity	C-224913-E	C / A2
			Class	SRCA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

254699 254702 254700 254701 254699-E 254700-E 254701-E 254702-E