
Butt connectors, Cu, F-series





- For fine and superfine stranded round conductors, e.g. to DIN EN 60228 Cl. 5 and 6
- Pipe dimension adjusted for fine and superfine stranded conductors
- Special wide opening for the easy entry of fine conductors

Characteristics

- Simple and safe processing due to butt mark
- Annealed material optimises material and crimping properties
- Simple cable entry due to internal chamfer

Material

- Copper (EN13600)

Surface

- Tin-plated to protect against corrosion

Technical instructions

- Tool: see page 42

Nominal cross section mm²	Part No.	Dimension mm			Weight/ 100 pcs. ~ kg	Packing unit/pcs
		d1	d4	l		
10	**722F**	5.5	8.0	38	0.90	100
16	**723F**	6.6	9.5	38	1.25	100
25	**724F**	7.9	11.0	38	1.56	50
35	**725F**	9.2	12.5	45	2.19	50
50	**726F**	11.0	15.0	45	3.37	50
70	**727F**	13.0	17.0	54	4.65	50
95	**728F**	14.5	19.0	56	6.05	25
120	**729F**	16.2	21.0	60	7.58	25
150	**730F**	18.0	23.0	68	9.83	10
185	**731F**	20.6	26.0	75	13.30	10